

Live VM Migration DTD Hardware



USO-240

Equipped with state-of-the-art storage drives, high performance processors, system memory, and built-in RAID controller the StoneFly DTD appliances make the VM migration quicker, reliable and efficient.

The DTD appliances are purpose-built for VMware environments and provide a "plug and play" experience for live VM migrations.

Note: USO appliances also support optional Fibre Channel (FC).
For details, contact StoneFly pre-sales engineers.

Components	Description (Standard + Optional)
Network Ports	1Gb & 10Gb RJ-45 iSCSI + NAS Connections (Backwards Compatible with 1Gb)
Available PCI-E Slots	Up to 2 PCI-E Slots Can be Used for Optional Network Card Upgrades Optional Support for 1Gb RJ-45, 10Gb RJ-45, SFP+, CX4, SR Optical, LR Optical, 40Gb QSFP+
Supported Storage Drives	12Gb SAS Drives: 7.2K RPM: 4TB, 6TB, 8TB, 10TB, 12TB, 14TB, 16TB 10K RPM: 1.2TB, 1.8TB, 2.4TB 15KRPM: 600GB, 900GB SSD (1x/3x/10x DWPD): 1x DWPD: 960GB, 1.9TB, 3.8TB, 7.6TB 3x DWPD: 800GB, 1.6TB, 3.2TB, 6.4TB 10x DWPD: Upon Request
Drive Bays	24 x 3.5"
Processor(s)	4-Core 9th Gen Intel Core i3 (Standard) Up to 8-Core 9th Gen Intel Core i7 (Optional)
System Memory	8GB (Standard) Up to 64GB (Optional)
NVMe SSD for OS	256GB (Standard) Up to 3.8TB (Optional)
RAID Controller	High-Performance Hardware RAID Controller Supports RAID Levels 0, 1, 5, 6, 10, 50, 60
Power Supply	Redundant 80-PLUS® 1200W Titanium Certified High Efficiency Hot-Swappable Power Supplies