

Live VM Migration DTD Hardware



USO-40T

Equipped with state-of-the-art storage drives, high performance processors, system memory, and built-in RAID controller the StoneFly DTD appliances make the VM migration quicker, reliable and efficient.

The DTD appliances are purpose-built for VMware environments and provide a "plug and play" experience for live VM migrations.

Note: USO appliances also support optional Fibre Channel (FC). For details, contact StoneFly pre-sales engineers.

Components	Description (Standard + Optional)
Network Ports	Dual Bonded 1Gb RJ-45 iSCSI + NAS Connections
Supported Storage Drives	6Gb SATA drives: 7.2K RPM: 2TB, 4TB, 6TB, 8TB, 10TB, 12TB, 14TB, 16TB
Drive Bays	4 × 3.5"
Processor(s)	4-Core 9th Gen Intel Core i3 (Standard) Up to 8-Core 9th Gen Intel Core i7 (Optional)
System Memory	8GB (Standard) Up to 32GB (Optional)
NVMe SSD for OS	256GB (Standard) Up to 3.8TB (Optional)
RAID Controller	High-Performance Hardware RAID Controller, Supports RAID Levels 0, 1, 5, 6, 10
Power Supply	80-PLUS® 250W Bronze Certified High Efficiency Hot-Swappable Power Supply